

SCAN COMBIFLEX 330 / 330RS

[WEBPAGE](#) →

[CONTACT](#) →

[MANUAL](#) →



The Scan Combiflex 330 is a powerful and easy to use machine, and is one of the most versatile machines on the market. The 330 mm/13 inch single grinding disc is effective for grinding smaller areas, edging long stretches of the floor, lite coating removal and surface prep.

A simple and quick adjustment allows the operator to change the configuration of the Scan Combiflex 330 from a small grinder into an edger, with the entire process taking less than one minute.

The 330 mm/13 inch disc on the Scan Combiflex 330 can be configured with 3, 6, or 9 of our metal, ceramic, or resin bond diamond tools. This allows the machine to cut more aggressively when necessary, or grind softer surfaces by spreading out the weight and using more tools.

For smooth and simple transport, the Scan Combiflex 330 can easily be separated into two parts, each weighing well under 100 lbs.

There are an optional 14.5 kg / 32 lbs weight available for Scan Combiflex 330. The weight kit only fits Scan Combiflex 330 1-phase 110 V/230 V and Scan Combiflex 330RS 1-phase 115 V.

The Scan Combiflex 330RS is equipped with adjustable speed.

EASY ADJUSTMENT TO EDGE GRINDER



GRINDING DISC
SINGLE



GRINDING WIDTH
330 mm / 13"



WEIGHT
65 kg (143 lbs) /
70 kg / 154 lbs

TECHNICAL DATA

SCAN COMBIFLEX 330

	1-phase	3-phase
Voltage:	110-120 V 1~ or 220-240 V 1~	400 V 3~
Motor power:	1,5 kW	4 kW
Current:	20 Amp. or 10 Amp	16 Amp.
Frequency:	60 Hz or 50 Hz	50-60 Hz
Grinding speed:	750 rpm or 600 rpm	1430 rpm
Grinding disc:	1 x 330 mm / 1 x 13"	1 x 330 mm / 1 x 13"
Grinding width:	330 mm / 13"	330 mm / 13"
Weight:	65 kg / 143 lbs.	65 kg / 143 lbs.
Other:	CE-marking	CE-marking

SCAN COMBIFLEX 330RS

	1-phase	3-phase
Voltage:	110-120 V 1~ or 220-240 V 1~	400 V 3~
Motor power:	1,1 kW or 1,5 kW	4 kW
Current:	15 Amp. or 10 Amp.	16 Amp.
Frequency:	50-60 Hz	50-60 Hz
Grinding speed:	150-400 rpm or 250-750 rpm	250-1500 rpm
Grinding disc:	1 x 330 mm / 13"	1 x 330 mm / 13"
Grinding width:	330 mm / 13"	330 mm / 13"
Weight:	70 kg / 154 lbs.	70 kg / 154 lbs.
Other:	CE-marking	CE-marking



Separates in two parts
for easy transportation

Weight kit available
for Scan Combiflex 330

Scan Combiflex 330RS
Variable speed
and two directions

Recommended
vacuum Scan
Combiflex 330/330RS:
Scan Dust 2900 or
Scan Dust 3600

Adjustable head
for edge grinding

SCANMASKIN
MACHINES—MINERALS—KNOW—HOW

Phone HQ: +46 31 99 49 70 • USA: +1 425 209 0147
Email HQ: info@scanmaskin.com • USA: info.usa@scanmaskin.com
www.scanmaskin.com